

CHARACTERISTIC OF THERMAL TRANSFER RIBBON

Brand Name - "STANDARD+"

Item code **KOD-SPxxx-yyy** OUT winding; xxx – width in mm, yyy – length in mm;
 KIP-SPxxx-yyy IN winding; xxx – width in mm, yyy – length in mm;

Product Description

STANDARD+ is premier wax, durable and popular. STANDARD+ offers high speed and high resolution printing for a wide variety of applications. STANDARD+ leads the industry in edge definition for clean, durable and dense bar codes. STANDARD+ is also designed according standard anti-static and back coat properties for print head protection.

Recommended Media

Coated/uncoated paper, synthetic paper, polyethylene, polypropylene, polyolefin, RAFLATAC®, JAC®, FASSON®, Valeron®, Polyart®.

Recommended Applications



General Shipping Logistics Inventory Shelf Flexible package Horticulture Pharmaceutical Retail

Performance Characteristics

- Increased durability
- Extensive label adaptability for expanded application options
- Excellent print quality for high – speed printing
- Anti – static for easy handling and print head protection
- Industry leading in Edge Definition™ for clean, durable and dense bar codes
- Specialty formulated back coating for print head protection

Ribbon Specification

Description	Technical Specifications
Ink	Wax
Color	Black
Ink Thickness	2.6 ± 0.4µ
Base Film Thickness	4.5µ
Ribbon Thickness	9.4 ± 0.7µ
Ink Melting Point	68°C - 70°C (154.4°F – 158.0°F)
Print Density	> 1.7

Ribbon Storage Conditions

Temperature	5°C to 35°C (41°F to 95°F)
Humidity	10% to 85% relative humidity
Light	Avoid direct sunlight

